

# TECHNICAL DATASHEET

## PEFS F3 / F3N LOP Manual Actuator

### Features

The Chubb PEFS F3 / F3N Manual Actuator features:

- Australian Standard compliant to AS5062
- Loss of Pressure piston operation
- Large strike push button for easy actuation in emergencies
- Transport style pull pin to prevent accidental operation.
- Stainless steel valve assembly
- Polyester powder coated stainless steel housing
- Pressure Indicator (1700kPa)
- Foil rupture release outlet to prevent ingress of dirt
- Charging Port



### Specifications

<b>Part Number</b>	47130	47131
<b>Description</b>	LOP Manual Actuator PEFS F3 / F3N	LOP Manual Actuator PEFS F3 / F3N Flush Mount
<b>Height</b>	181 mm	142 mm
<b>Width</b>	129 mm	70 mm
<b>Depth</b>	75 mm	60 mm
<b>Height of Piston above flush mount</b>	-	64mm
<b>Working Pressure</b>	1700 kPa	1700 kPa
<b>Mass</b>	1.52 kg	0.62 kg
<b>Actuation Thread</b>	7/16" JIC	7/16" JIC
<b>Charging Port</b>	Schrader Valve	Schrader Valve

### Service Requirements

Service in accordance with the PEFS F3 Maintenance Manual, PEFS F3N Maintenance Manual and Australian Standard AS5062

An Actuator Service Kit (Part No: 28038) is available for the purpose of servicing the LOP Manual Actuators.

Rupture Nozzle should be replaced after use or if foil shows signs of damage and or corrosion.

### Spare Parts List

